

DB20P --- VOICE OTP DEMO BOARD USER MANUAL

For aP89042 (42") / aP89021 (21") / aP89010 (10")

	Durations	PHRASE		TG - pin	PDIP	SOP	DIE	VCC
		Key mode	CPU mode					
aP89042	42"	32	32	8	20	20	YES	2.2 ~ 3.6V
aP89021	21"	12	12	4	16	16	YES	2.2 ~ 3.6V
aP89010	10"	12	12	4	16	16	YES	2.2 ~ 3.6V

Part No. : DB20P
VCC-3V

PWM out for aP89042

VCC-3V

SBT PLAY key

for aP89042/aP89021/aP89010 DIP-16

1. Part no. : **AP89XS-DB20P**
2. PCB SIZE : 36 x 24 mm
3. PCB NO. : SZ6003

4. VCC = 3V
5. Only PWM
6. SBT PIN PLAY

Sampling rate	Rosc	Sampling rate	Rosc	Sampling rate	Rosc
4.9 K Hz	300K	7.46 K Hz	220K	11 K Hz	140K
5.26 K Hz	290K	7.70 K Hz	210K	11.76 K Hz	130K
5.88 K Hz	280K	8.06 K Hz	200K	12.5 K Hz	120K
6.09 K Hz	270K	8.47 K Hz	190K	13.33 K Hz	110K
6.33 K Hz	260K	8.93 K Hz	180K	14.51 K Hz	100K
6.67 K Hz	250K	9.26 K Hz	170K	15.63 K Hz	91K
6.85 K Hz	240K	9.80 K Hz	160K	16.95 K Hz	82K
7.14 K Hz	230K	10.42 K Hz	150K	18.18 K Hz	75K

** The above Table is for reference only

APLUS INTEGRATED CIRCUITS INC.

TEL : 886-2-2782-9266

FAX : 886-2-2782-9255

<http://www.aplusinc.com.tw>

E-mail: sales@aplusinc.com.tw